

# Windspill™ Deluxe Adjustable Banner Hardware

Pictured are two #5501A Deluxe Adjustable Single Bracket Sets. These two sets will mount one banner up to 36" in width and 96" in length. Minimum 2½" pole sleeves top and bottom are required.

**BASE UNIT** – Cast of 356 aluminum alloy with a T-51 heat treatment. Weight = 1 lb. The weight and design of the Base Unit provide a strong foundation for the mounting system.

1. The Base Unit is secured to a pole with a double wrap of ¾" #206 stainless steel banding (note the guide channels at either end to prevent movement of the banding). Also, the Base Unit may be lag-bolted to a wood pole or a wall surface through the two 5/8" holes at either end. NOTE: If the Base Unit is lag-bolted to a surface, the Arm Unit will pass over the lag bolt heads for easy removal and adjustment.
2. Two ¾" long x 3/8" diameter self-locking bolts pass through the adjustment slots in the Arm Unit and thread into the Base Unit, thereby, safely securing the Arm Unit to the Base Unit.
3. The "T" formation at the top of the Base Unit allows the Arm Unit to slide into the channels of the Base Unit. The weight of the Arm unit will hold it in the channel while the bolts are being installed.
4. The 3" width and 7¾" length of the Base Unit provide lateral and vertical stability for the system. The large surface area also allows a secure attachment to the pole or wall surface (ie: no "creeping" up or down or side-to-side movement on the pole).
5. The radius on the backside of the Base Unit is designed so it will fit snugly on 3½" diameter and larger round poles (including fluted poles). The flat edges on the backside allow the Base to securely mount to square and octagonal poles, or wall surfaces.
6. The Base Unit does not require a confusing "top end up" mount as with some systems on the market. Both ends are the same and it doesn't matter which end is up or down.
7. Available in rod lengths to fit 18", 24", 30" and 36" wide banners.
8. Five Year Warranty.

